



25kV(24kV、20kV) 棒形悬式复合绝缘子示意图  
25kV(24kV、20kV) Composite Long Rod Suspension Type Insulator Schematic Diagram

25kV(24kV、20kV) 棒形悬式复合绝缘子主要尺寸与特性  
Main Dimensions and Characteristics of 25kV(24kV、20kV) Composite Long Rod Suspension Type Insulator

Serial Number 序号	Type of Insulator 绝缘子型号	Specified Voltage 额定电压	Specified Mechanical Tensile Load 额定机械拉伸负荷	Section Length 绝缘子长度	Min. Arcing Distance 最小电弧距离	Big Shed Diameter 大伞直径	Min Nominal Creepage Distance 最小公称爬电距离	Lightning Impulse Withstand Voltage(Peak Value) 雷电冲击全波耐受电压(峰值)	Power Frequency Withstand Voltage Min. Wet(PMS) 工频(全波)耐受电压(湿态)	Preference Weight 参考重量
		kV	kN	H mm	h mm	d1 mm	L mm	≧ kV	≧ kV	kg
1	FXBW-25(24/20) (120/100/80/70)	25/24/20	120/100 80/70	504 ± 15	300	121	900	150	90	2.0

说明：产品的尺寸、特性、连接方式和伞裙颜色等可按照客户具体要求设计、生产  
Note: Product's dimension, characteristics, connecting type, shed color, etc can be designed and manufactured in accordance with customer's requirements.