

整体腕臂支撑复合绝缘子 Overall Bracket Support Composite Insulator



整体腕臂支撑复合绝缘子主要尺寸与特性

Main Dimension and Characteristics of overall Bracket Support Composite Insulator

序号 Serial Number	产品型号 Product Type	额定电压 Specified Voltage	额定机械负荷 Specified Mechanical Tensile Pulling Load	绝缘长度 Section Length	最小绝缘距离 Min insulation Distance	最小公称爬电距离 Min nominal Creepage Distance	雷电冲击耐受电压(峰值) Lightning Impulse Withstand Voltage (Peak Value)	人工污秽耐受电压 (盐沉积密度: 50mg/cm ²) Artificial Pollution Power Frequency Withstand Voltage (Salt Deposit Density: 50mg/cm ²)	工频耐受电压 Power Frequency Withstand Voltage Test - Wet
		kV	kN	H mm	h mm	L mm	kV	kV	kV
1	FQBG-25/8	25	8	670±L	480	1600	270	32	130
2	FQBG-25/12	25	12	670±L	480	1600	270	32	130
3	FQBG-25/16	25	16	670±L	480	1600	270	32	130
4	FQBSG-25/8	25	8	760±L	480	1600/145	270	32	130
5	FQBSG-25/12	25	12	760±L	480	1600/145	270	36	130
6	FQBSG-25/16	25	16	760±L	480	1600/145	270	36	130

说明: 产品的尺寸、特性、连接方式和伞裙颜色等可按照客户具体要求设计、生产

Note: Product's dimension, characteristics, connecting type, shed color, etc can be designed and manufactured in accordance with customer's requirements.