

刚性悬挂用复合绝缘子 Rigidity Suspension Composite Insulator



刚性悬挂用复合绝缘子主要尺寸与特性

Main Dimension and Characteristics of rigidity Suspension Composite Insulator

序号 Serial Number	产品型号 Product Type	额定电压 Specified Voltage	额定机械拉伸负荷 额定机械破坏负荷 Specified Mechanical Tensile Pulling Load Nominal Mechanical Failure Load	额定机械弯曲负荷 Specified Mechanical Bending Load	绝缘长度 Section Length	最小绝缘距离 Min Insulation Distance	最小公称爬电距离 Min nominal Creepage Distance	雷电冲击耐受电压(峰值) 雷电冲击耐受电压 Lightning Impulse Withstand Voltage (Peak Value) Lightning Impulse Withstand Voltage	工频耐受电压 Power Frequency Withstand Voltage Test - Wet
		kV	kN	kN	H mm	h mm	L mm	kV	kV
1	FZS-1.5/9	1.5	50	13	110	110	250	125	30

说明：产品的尺寸、特性、连接方式和伞裙颜色等可按照客户具体要求设计、生产

Note: Product's dimension, characteristics, connecting type, shed color, etc can be designed and manufactured in accordance with customer's requirements.