

单绝缘腕臂支撑复合绝缘子 Single Insulation Bracket Support Composite Insulator



单绝缘腕臂支撑复合绝缘子主要尺寸与特性

Main Dimension and Characteristics of Single Insulation Bracket Support Composite Insulator

Serial Number 序号	Product Type 产品型号	Specified Voltage 额定电压	Specified Mechanical Breaking Load 额定机械破坏荷载	Specified Mechanical Tensile Force 额定机械破坏荷载	Section Length 绝缘长度	Min Insulation Distance 最小绝缘距离	Min nominal Creepage Distance 最小公称爬电距离	Lightning Impulse Withstand Voltage(Peak Value) 额定雷电冲击电压峰值	Artificial Pollution Power Frequency Withstand Voltage (Salt Deposit Density) 额定污秽闪络电压(kV) (盐密)	Power Frequency/Withstand Voltage Test-Wei 工频耐受电压
		kV	kN	kN	H mm	h mm	L mm	kV	kV	kV
1	FQB-25/(8/12)	25	8/12	80/100	760	490	1200	270	/	130
2	FQB-25/(16/20)	25	16/20	120	900	490	1200	270	/	130
3	FQBJ-25/(8/12)	25	8/12	80/100	760	490	1400	290	32	140
4	FQBJ-25/(16/20)	25	16/20	120	800	490	1400	290	32	140
5	FQBG-25 (8/12)	25	8/12	80/100	800	520	1600	310	36	150
6	FQBG-25 (16/20)	25	16/20	120	900	520	1600	310	36	150

说明：产品的尺寸、特性、连接方式和伞裙颜色等可按照客户具体要求设计、生产

Note: Product's dimension, characteristics, connecting type, shed color, etc can be designed and manufactured in accordance with customer's requirements.